

ALQ-EPKITIP-8-2

8 Channel IP NVR, 2x IP Bullet Camera Kit



DELIVERING GREAT VALUE



1080P

2
Camera
Kit

Up to
3TB HDD
Storage

8CH

The ALQ-EPKITIP-8-2 includes everything you need to install a full IP Plug and Play CCTV system including: 8 Channel NVR, 2x bullet cameras, cabling, power supply and USB mouse. Additional cameras sold separately.

ORDER CODES
ALQ-EPKITIP-8-2/1000
ALQ-EPKITIP-8-2/3000

4 & 16 CHANNEL EP KIT ALSO AVAILABLE


- ALQ-EPRIP-8 KEY FEATURES**
- 8 Channel
 - Mobile Viewing (FreecamPro APP)
 - 1080p Resolution
 - HDMI & VGA Output
 - Up to 3TB HDD Storage
 - H.264 Compression

- KIT INCLUDES**
- 1x 8ch IP POE NVR
 - 1x 1m HDMI
 - 2x 2MP IP Bullet Cameras
 - 1x UK Kettle Lead
 - 2x 20m lengths of premade CAT5
 - 1x DC48V 2A PSU
 - 1x Mouse
 - 1x Quick operation manual

- ALQ-EPBULLET-IP KEY FEATURES**
- 1/3" CMOS
 - 36 LEDs
 - 2MP
 - 4 Privacy Masks
 - 3.6mm Fixed Lens
 - IP66
 - 25m IR Range
 - 171mm x ø65mm

MODEL	ALQ-EPRIP-8	
	Operating System	Embedded Linux
VIDEO	Video Compression	H.264
	Video Input	8ch 1920 x 1080
	Video Output Resolution	1920 x 1080
	Display Views	1, 4, 8 Split
	Playback Resolution	1920 x 1080
	Video Output	HDMI, VGA
RECORD	Record Video	8ch 25FPS @ 1080P
	Simultaneous Playback	1x 1080P, 4x D1
	Record Mode	Manual, Motion, Schedule
CONTROL	USB	Mouse
INTERFACE	WAN/LAN	1x RJ45
	USB 2.0	1x USB Ports
	POE Port	8x RJ45 Ports
STORAGE &	SATA	1x Internal HDD
BACK UP	Max. HDD	1TB or 3TB
	Back Up	USB 2.0
GENERAL	Power Supply	DC48V 2A
	Power Consumption	Max 18W inc HDD (Not inc. POE)
	Operating Temperature	0C ~ +55C
	Operating Humidity	10% ~ 90%
	Dimensions	(W) 300mm x (D) 210mm x (H) 48mm
REMOTE	Remote Connections	5
MONITORING	Mobile	iOS, Android
	Network	1x RJ45 10M/100M/1000M
	P2P	Yes

MODEL	ALQ-EPBULLET-IP	
	Sensor	1/3" CMOS
	Video Compression	H.264
	Video System	Pal/NTSC
	Effective Pixel	1920 x 1080
	Max Frame	25FPS
	S/N Ratio	≤38.3dB
	Lens	3.6mm
	IR LED (pcs)	36 pcs
	IR Distance	25m
	IR Wave Length	850nm
	IR LED Auto Switch	Day/Night, On/Off
	Min Illumination	Colour (0.01Lux/F1.6 (AGC on)) Mono (0.002lux/F1.6(AGC on))
	ATW	Auto/Manual
	Shutter Speed	1/100 - 1/100000
	AGC	Auto
	White Balance	Auto
	WDR	Off/On
	BLC	Off/On
	Image Flip	Normal/ Vertical/ Horizontal/ Vertical and Horizontal
	Day/Night	Auto/ Colour/ Mono(ICR)
	Main Stream	1920 x 1080, 1280 x 720
	Sub Stream	D1, VGA, QVGA
	Bit Rate	Upto 8Mbps CBR/VBR
	Audio Compression	G.711
	Privacy Mask	4 masks
	Image Setting	Adjust from IE
	Protocol	ONVIF, GB/T28181
	Axis	Bi
	IP Rating	IP66
	Power Supply	POE / 12V DC
	Power Consumption	Max 10W
	Operating Temperature	-20C ~ +60C
	Operating Humidity	≤95%
	Weight	0.47kgs
	Certifications	CE, FCC, ROHS
	Dimensions	171mm x ø65mm



Download the **FreecamPro** app on the iOS and Android app stores to remotely monitor your CCTV from your smartphone or tablet.

